Package: Rspc (via r-universe)

October 31, 2026

Type Package

Title Nelson Rules for Control Charts

Version 1.2.2

Author Martin Vagenknecht (MSD) [aut], Jindrich Soukup (MSD) [aut], Stanislav Matousek (MSD) [aut, cre], Janet Alvarado (MSD) [ctb, rev]

Maintainer Stanislav Matousek <rspc@merck.com>

Description Description: Rspc is an implementation of nelson rules for control charts in R. The Rspc package implements some Statistical Process Control methods, namely Levey-Jennings type of I (individuals) chart, Shewhart C (count) chart and Nelson rules. Typical workflow is taking the time series, specify the control limits, and list of Nelson rules you want to evaluate. There are several options how to modify the rules (one sided limits, numerical parameters of rules, etc.). Package is also capable of calculating the control limits from the data (so far only for i-chart and c-chart are implemented).

Depends R (>= 3.1.0)

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

VignetteBuilder knitr

Suggests knitr

Repository https://merck.r-universe.dev

Date/Publication 2018-07-19 16:56:49 UTC

RemoteUrl https://github.com/merck/spc_package

RemoteRef HEAD

RemoteSha 752bc37e8b1edf13c38ffce30f2d9af95dd4a14c

Contents

CalculateLimits 2
CalculateZoneBorders 3
EvaluateRules 4
NelsonRules 5
Rule1 6
Rule2 7
Rule3 7
Rule4 8
Rule5 9
Rule6 10
Rule7 11
Rule8 12
SetParameters 13

Index **14**

`CalculateLimits` *CalculateLimits*

Description

Evaluates whether to use custom limits or calculate them from the data.

Usage

```
CalculateLimits(x, lcl = NA, cl = NA, ucl = NA, type = "i",
  controlLimitDistance = 3)
```

Arguments

`x`	Numerical vector
`lcl`	Lower control limit, single value or NA
`cl`	Central line, single value or NA
`ucl`	Upper control limit, single value or NA
`type`	Type of control chart, either "i" for i-chart (default) or "c" for c-chart
`controlLimitDistance`	Multiple of st.dev to be used to calculate limits, possible values: 1, 2, 3 (default); this parameter affect the interpretation of lcl and ucl parameters

Details

If at least two limits were provided, the missing ones are calculated from the them. If one or zero limits were provided the rest is computed from data.

Value

Named list with limits

Examples

```
CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
```

`CalculateZoneBorders` *CalculateZoneBorders*

Description

Some Nelson rules uses so-called zones. This function calculates the borders of the zones for given limits.

Usage

```
CalculateZoneBorders(limits, controlLimitDistance = 3)
```

Arguments

`limits`	List of limits provided by `CalculateLimits`
`controlLimitDistance`	Multiple of st.dev to be used to calculate limits, possible values: 1, 2, 3 (default); this parameter affect the interpretation of lcl and ucl parameters

Value

Vector of zones

Examples

```
limits = CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
CalculateZoneBorders(limits)
#limits is object created by CalculateLimits() function
```

EvaluateRules *EvaluateRules*

Description

Evaluates the selected Nelson rules for a given numerical vector.

Usage

```
EvaluateRules(x, type = "i", whichRules = 1:8, lcl = NA, cl = NA,
  ucl = NA, controlLimitDistance = 3, returnAllSelectedRules = F,
  parRules = NULL)
```

Arguments

x	Series to be evaluated, numerical vector
type	Type of control chart, either "i" for i-chart (default) or "c" for c-chart
whichRules	Selection of Nelson rules beeing evaluated, vector with numbers from 1 to 8
lcl	Lower control limit, single numeric value (expected as mean - controlLimitDistance * sigma), if missing the function calculates it from data
cl	Central line, single numeric value (expected as mean), if missing the function calculates it from data
ucl	Upper control limit, single numeric value (expected as mean + controlLimitDistance * sigma), if missing the function calculates it from data
controlLimitDistance	Multiple of st.dev to be used to calculate limits, possible values: 1, 2, 3 (default); this parameter affect the interpretation of lcl and ucl parameters
returnAllSelectedRules	Resulting dataframe will contain all selected rules, either True or False, if missing only valid rules returned
parRules	Optional parameters for specific rules, for details see SetParameters

Details

Only Rules 1-4 relevant for c-chart.
Check for non negative data for c-chart.
For controlLimitDistance less than or equal to 2 disable rule 5.
For controlLimitDistance less than or equal to 1 disable rule 5,6,8.
For returnAllSelectedRules=TRUE columns of invalid rules for given evaluation are filled with NAs.

Value

Dataframe containing original vector and rules evaluation

Examples

```
# Evaluate data, use all 8 Nelson rules, limits are specified by user
EvaluateRules(x = rnorm(10), whichRules = 1:8, lcl = 0, cl = 50, ucl = 100)
#Evaluate only rule 1, 3, 5, calculate limits from data using c-chart formula,
#use 2 sigma instead of 3, modify default behaviour of rule by pars variable
#created by function SetParameters()
pars = SetParameters()
EvaluateRules(x = rpois(10, lambda = 15), type = 'c', whichRules = c(1,3,5), lcl = NA, cl = NA,
ucl = NA, controlLimitDistance = 2, parRules = pars)
# pars is object of optional parameters created by SetParameters() function
```

`NelsonRules` *NelsonRules*

Description

Auxiliary function to calling individual Rule functions.

Usage

```
NelsonRules(ruleN, data, zoneB, limits, parRules = NULL, ...)
```

Arguments

`ruleN`	Name of individual Rule function "Rule1" to "Rule8"
`data`	Data to be checked, numerical vector
`zoneB`	Vector of zones created by `CalculateLimits`
`limits`	List of limit created by `CalculateLimits`
`parRules`	List of optional parameters for this particular rule
`...`	unspecified arguments of a function

Details

Handling the missing values:

Missing values are represented by the symbol NA - not available.

Rule 1: NAs do not violate this rule.

Rule 2-8: NAs are ignored, they do not break Rule evaluation. NA values are removed from the vector, the rule function is calculated and then the NAs are returned back to it's original position in the vector.

Value

Result of individual Rule function with predefined parameters

`Rule1` *Rule 1*

Description

One point beyond the control limits

Usage

```
Rule1(x, lcl, ucl, sides, ...)
```

Arguments

`x`	Numerical vector
`lcl`	Lower control limit, single number
`ucl`	Upper control limit, single number
`sides`	Monitored side of the process: either "two-sided" (default), "upper" or "lower"
`...`	unspecified arguments of a function

Details

0 means: ok
1 means: violation

inequality used during evaluation

parametr sides is internally encoded as: 1 for "two-sided", 2 for "upper", 3 for "lower"

Value

Vector of the same length as x

Examples

```
Rule1(x = rnorm(10), lcl = 10, ucl = 100, sides = "two-sided")
```

Rule2 *Rule 2*

Description

Nine points in a row are on one side of the central line.

Usage

```
Rule2(x, cl, nPoints = 9, ...)
```

Arguments

x	Numerical vector
cl	central line, single number
nPoints	Sequence of consequtive points to be evaluated
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

inequality used during evaluation

Value

Vector of the same length as x

Examples

```
Rule2(x = rnorm(20), cl=0, nPoints = 9)
```

Rule3 *Rule 3*

Description

Six points in a row steadily increasing or decreasing.

Usage

```
Rule3(x, nPoints = 6, convention = 1, equalBreaksSeries = 1, ...)
```

Arguments

x	Numerical vector
nPoints	Sequence of consequtive points to be evaluated
convention	Calculation according to 'minitab' or 'jmp' (see details)
equalBreaksSeries	Equal values break consequtive series of points
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

parameter equalBreakSeries is internally encoded as: 1 for TRUE and 2 for FALSE

parameter convention is internally encoded as: 1 for 'minitab' and 2 for 'jmp'

Difference in convention parameter is as follows:
'minitab' - seven points in a row steadily increasing or decreasing
'jmp' - six points in a row steadily increasing or decreasing

Value

Vector of the same length as x

Examples

```
Rule3(x = rnorm(20), nPoints = 6, convention = 1, equalBreaksSeries = 1)
```

Rule4 *Rule 4*

Description

Fourteen or more points in a row alternate in direction, increasing then decreasing.

Usage

```
Rule4(x, nPoints = 14, convention = 1, ...)
```

Arguments

x	Numerical vector
nPoints	Sequence of consequtive points to be evaluated
convention	Calculation according to 'minitab' or 'jmp' (see details)
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

parameter convention is internally encoded as: 1 for 'minitab' and 2 for 'jmp'

Difference in convention parameter is as follows:
'minitab' - 15 or more points (14 changes of direction) in a row alternate in direction, increasing then decreasing
'jmp' - 14 or more points (13 changes of direction) in a row alternate in direction, increasing then decreasing

Value

Vector of the same length as x

Examples

```
Rule4(x = rnorm(20), nPoints = 14,convention = 1)
```

Rule5 *Rule 5*

Description

Two out of three consecutive points beyond the 2*sigma limits on same side of center line.

Usage

```
Rule5(x, zoneB, minNPoints = 2, nPoints = 3, ...)
```

Arguments

x	Numerical vector
zoneB	Vector of zone borders
minNPoints	Minimal number of points in a sequence violating a rule
nPoints	Sequence of consequtive points to be evaluated
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

inequality used during evaluation
Rule is violated also if the first two points are beyond the 2*sigma limits During calculation of EvaluateRules function wiht controlLimitDistance <= 2, the evaluation of this rule is suppressed

Value

Vector of the same length as x

Examples

```
limits = CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
zones = CalculateZoneBorders(limits)
Rule5(x = rnorm(20), zoneB = zones, minNPoints = 2, nPoints = 3)
#zones is object created by function CalculateZoneBorders()
```

Rule6 *Rule 6*

Description

Four or five out of five points in a row are more than 1 standard deviation from the mean in the same direction.

Usage

```
Rule6(x, zoneB, minNPoints = 4, nPoints = 5, ...)
```

Arguments

x	Numerical vector
zoneB	Vector of zone borders
minNPoints	Minimal number of points in a sequence violating a rule
nPoints	Sequence of consequtive points to be evaluated
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

inequality used during evaluation Rule is violated also if the first four points are beyond the 1 standard deviation from the mean During calculation of EvaluateRules function wiht controlLimitDistance <= 1, the evaluation of this rule is suppressed

Value

Vector of the same length as x

Examples

```
limits = CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
zones = CalculateZoneBorders(limits)
Rule6(x = rnorm(20), zoneB = zones, minNPoints = 4, nPoints = 5)
#zones is object created by function CalculateZoneBorders()
```

Rule7 *Rule 7*

Description

Fifteen points in a row are all within 1 standard deviation of the mean on either side of the mean.

Usage

```
Rule7(x, nPoints = 15, zoneB, ...)
```

Arguments

x	Numerical vector
nPoints	Sequence of consequtive points to be evaluated
zoneB	Vector of zone borders
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

equality used during evaluation

Value

Vector of the same length as x

Examples

```
limits = CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
zones = CalculateZoneBorders(limits)
Rule7(x = rnorm(20), zoneB = zones, nPoints = 15)
#zones is object created by function CalculateZoneBorders()
```

Rule8 *Rule 8*

Description

Eight points in a row outside 1 standard deviation of the mean in both directions.

Usage

```
Rule8(x, nPoints = 8, zoneB, ...)
```

Arguments

x	Numerical vector
nPoints	Sequence of consequtive points to be evaluated
zoneB	Vector of zone borders
...	unspecified arguments of a function

Details

0 means: ok
1 means: violation

inequality used during evaluation During calculation of EvaluateRules function wiht controlLimitDistance <= 1, the evaluation of this rule is suppressed

Value

Vector of the same length as x

Examples

```
limits = CalculateLimits(x = rnorm(10), lcl = NA, cl = 100, ucl = NA, type = 'i')
zones = CalculateZoneBorders(limits)
Rule8(x = rnorm(20), zoneB = zones, nPoints = 8)
#zones is object created by function CalculateZoneBorders()
```

SetParameters *SetParameters*

Description

Creates optional parameters with default settings.

Usage

```
SetParameters()
```

Details

The function is called without any parameter. If you want to modify any or the rules' setting, modify the result of this function and plug it to EvaluateRules's parRules parameter.

Value

List of optional parameters

Examples

```
pars <- SetParameters()
pars$Rule1$sides <- "upper"
#function doos not need any input parameters
```

Index

CalculateLimits, 2, *3*, *5*
CalculateZoneBorders, 3

EvaluateRules, 4, *13*

NelsonRules, 5

Rule1, 6
Rule2, 7
Rule3, 7
Rule4, 8
Rule5, 9
Rule6, 10
Rule7, 11
Rule8, 12

SetParameters, *4*, 13